

SPECIFICATION FOR DRIZIT® MAINTENANCE SOCKS

	0330/125/10	0330/125/20	0330/125/40	0330/300/5	0230/600/4
Size	7.5cm dia x 1.25m	7.5cm dia x 1.25m	7.5cm dia x 1.25m	7.5cm dia x 3m	7.5cm dia x 6m
Colour	Grey	Grey	Grey	Grey	Grey
Pack Quantity	10	20	40	5	4
Pack Wt (gross)	3.3 kg	5.4 kg	10.8 kg	4.1 kg	6.5 kg
Pack Size	50 x 35 x 18 cm	50 x 45 x 40 cm	85 x 45 x 45 cm	30 x 47 x 47 cm	50 x 50 x 50 cm
Sorbency (pack)	25 - 36 litres	50 - 72 litres	100 - 144 litres	30 - 42 litres	48 - 60 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using water. Higher figure based on high viscosity liquid with no drain

(Con)	Outer Casing:	100% polypropylene spun-bonded Tensile strength (mean): 400N (200mm strip/EN ISO 10319) UV resistant	
	Filler:	Natural and/or synthetic fibre	
and a second sec	Fitted With:	Polypropylene thread tails for joining	
	Pack Type:	Bag	
Compatibility:	May be safely used with all aqueous solutions and liquids immiscible with water, such as hydrocarbons, solvents, mineral oils, <i>with the exception of strong oxidising agents.</i> Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.		
Fire Resistance:	Good. (Physically flame-retardant) Incinerable to zero ash.		
Disposal:	Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.		
Safety Data:	Refer to our Safety Data Sheet. This product is non-toxic to users and to aquatic life. Further technical advice is available if required.		
Note:	All weights, dimensions, and other figures quoted are approximate.		

Revision Date: 06/11/2018



